

Care & Cleaning Guidelines: Flexible Skirtings and Transitions

Material Type – Polyvinylchloride (PVC):

For all PVC Accessories & Trims: Sit-on/Set-in skirting/Flat Skirting and Buffer Strips

- Skirtings should first be cleaned with a mild detergent solution using a sponge or damp cloth but avoid excessive moisture.
- Rinse with clean water being careful not to over wet.
- Dry off and buff up with lint free cloth.

For all PVC Transitions Profiles: Ramps, Trims, Cover Joints and Top Line (EBS, QMS, QR, QTL, QCJ, QD, QR, QTR)

- Cleaned with a mild detergent solution.
- Dry off if necessary with lint free cloth.

Always ensure safety: Do not traffic whilst wet!

Do not use highly alkaline or acidic cleaning agents. The pH of the cleaning agents should be between pH 5 and pH 12. If cleaning agents are applied at more than pH 10, the PVC material should be rinsed with pH neutral (pH 6 to pH 8) solution afterwards.

Safety Data Sheet PVC:

<https://www.quantumprofilesystems.com/uploads/quantum-flooring---sds-flexible-pvc-profiles.pdf>

Product Data Sheet Transitions:

<https://www.quantumprofilesystems.com/uploads/quantumflooringdatasheettransitionswinter2017.pdf>

We can confirm that all Quantum Flooring extruded products do not contain any substances classified as Substances of Very High Concern (SVHC) and as such are classed as REACH compliant.

If you require any further details please e-mail technical@quantum-ps.co.uk

Quantum Profile Systems Ltd / June 2018